



GROOMER INSTALLATION GUIDE

Congratulations on your purchase of a Groomer from Hatfield Manufacturing!

Follow these steps to install your groomer on your tractor

Note: Your groomer kit was designed to fit your JOHN DEERE 5 SERIES tractor, but the install process is virtually identical across most open-station/cab makes and models.

Kit Includes:

(1x) Bolt Kit

(1x) Main Groomer Assembly

(1x) Front Bumper

(1x) Rear Spacer (1 Per Implement)

(2x) Front spacers

(1x) Exhaust Bracket (2023-Present Models)

(1x) Valve Stand (If no cab)

**Before beginning install process READ ALL WARNINGS,
SAFETY PRECAUTIONS, AND SAFETY STICKERS**
Refer to website for maintenance, bolts, and hydraulics information

Step One:

Locate the **6** bolt holes we will be using on the right-hand side, left-hand side (for 2 implements), and **4** bolt holes for the front bumper of the tractor. They may have bolts or plastic inserts in them that will need to be removed. No drilling should be required. Also, check the fit of the bolts provided prior to moving the main blade assembly into place.




Step Two:

If 1 implement have the spacers in the general area for assembly. Then bring the Main Groomer Assembly up to the tractor and attach them loosely to the side and the front of the tractor as shown ensuring front and rear spacers are in the correct spots. The brush guard attaches to the front using the same bolts, it can also be added now. Don't fully tighten while mounting the implements.


If 2 implements bring the right-side implement first, then left-side implement. Don't forget the rear spacer for the 2nd implement. The brush guard attaches to the front using the same bolts, it can also be added now. Don't fully tighten while mounting the implements.


If an open-station model attach the valve stand during this time. If 2023 or newer model attach exhaust bracket.



Step Three:

Attach hydraulic cylinders at both ends if it isn't already and tighten everything down.





- Specification
- Oil line fittings
- (E-C) Torque.....37 N-m (27 lb-ft)

- Toll Free: 1.800.359.8171
Fax: 1.208.934-8892